


Single-row tapered roller bearings



Designation	Principal Dimensions(mm)					Basic Load Ratings		Limited Speed		Weight(kg)
	d	D	B	C	T	Dynamic	Static	Grease	Oil	
33001	9.4	24	12	12	13	6.8	7.4	13000	16100	0.032
30101X2YA	12	27	12	11	13	9	10.6	12400	15400	0.04
30202E	15	35	11	10	11.75	11.2	10.9	11900	15000	0.054
32102X	15	30	12	11	13	11.8	12.5	11400	14500	0.036
32202	15	35	15	11.75	15	20.3	23.1	11000	14000	0.074
30202U	15	35	13.5	11	13.5	17.7	19.5	11200	14100	0.052
32202	15	35	15	11.75	15	20.3	23.1	1100c	14000	0.074
30203	17	40	12	11	13.5	21.6	21.7	9600	12100	0.08
32004E	20	42	15	12	15	26.5	30.3	7400	9400	0.098
30204U	20	47	15	11.5	15	29.5	30.5	8300	10500	0.125
STA2047	20	47	17.5	13	17	32.7	36.2	8500	10700	0.145
CRD495	22	47	21	16	20	39.4	45.6	8200	10400	0.166
33006X2	30	58	20	15.5	20	53.4	62.6	6400	8100	0.227
32206X3	30	65	22	17.5	22	60.1	72.7	6500	8200	0.344
32206U	30	62	20	16	20	53.4	62.6	6400	8100	0.274
32207U	35	72	24	20	24.25	78.7	94.6	5500	6900	0.464